

ENGINEERED TO SERVE

FR Pioneer II

Our Pioneer II is the original feature-packed Type II ambulance. Built on a durable ProMaster 2500 159" chassis with 8,900 lbs GVWR, the Pioneer II meets or exceeds KKK-A-1822F and CAAS GVS requirements.



Standard Features

- Ten 15.5"-deep cabinets, all aluminum and LED-lit
- 3.000-watt full sine wave inverter
- Eight 110V dual outlets with 4 USB ports
- Tri-mode LED cabin lighting
- Locking meds safe
- Deep-cycle backup battery
- No-idle HVAC system
- Advanced electrical system
- · Digital main O2 system with auto shutoff
- · Easy-load main tank
- · Rear flip-up step
- Auto-eject shore power
- 35,000-lumen emergency lights
- 6-point restraints

Options

EKG monitor slide-out drawer

Command seat upgrades

UV sanitizer

Independent rooftop A/C

Shoreline heating & cooling

Additional deep-cycle battery

Additional outlets

RFID locking med box

IV solution heating/cooling unit

Retention systems

Electrical option pre-wires

Yellow grab handles

> EXTERIOR
















> INTERIOR








Why Pioneer II?

- Best-in-class value
- ✓ Safest Type II available
- Crash tested Safety tech package included
- Most efficient ambulance on the market
- EMT-engineered working environment
- Most comfortable patient area in a Type II
- Ambulance system reduces squad workload
- ✓ Industry-leading 6' 4" interior height with low 8' 6" exterior clearance
- ✓ 21" load height and 36' turning radius
- ✓ 5 year / 100,00-mile powertrain warranty





Engineered to Serve.



frconversions.com

CONTACT US

1231 Tech Court Westminster, MD 21157 (844) 372-8267 | sales@frconversions.com